




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 11/00		A2	(11) International Publication Number: WO 99/39499
			(43) International Publication Date: 5 August 1999 (05.08.99)
(21) International Application Number: PCT/US99/02238 (22) International Filing Date: 2 February 1999 (02.02.99) (30) Priority Data: 60/073,443 2 February 1998 (02.02.98) US (71) Applicant (for all designated States except US): PULSEPOINT COMMUNICATIONS [US/US]; 6307 Carpinteria Avenue, Carpinteria, CA 93013 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): CASTAGNA, William, D. [US/US]; 122 Descanso Avenue, Ojai, CA 93023 (US). (74) Agent: MONROE, Wesley, W.; Christie, Parker & Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published Without international search report and to be republished upon receipt of that report.

(54) Title: VOICE MAIL SYSTEM AND METHOD WITH SUBSCRIBER SELECTION OF AGENT PERSONALITIES, TELEPHONE USER INTERFACE ADDRESS BOOK AND TIME ZONE AWARENESS



(57) Abstract

To implement a voice mail system with time zone awareness, the phone number of the phone from which an incoming call is made is detected. After consulting a database relating portions of phone numbers with time zones, the difference in time zone between the detected telephone number of the calling party and the time zone of the call receiving party, is determined.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

1
VOICE MAIL SYSTEM AND METHOD WITH
SUBSCRIBER SELECTION OF AGENT PERSONALITIES, TELEPHONE USER
INTERFACE ADDRESS BOOK AND TIME ZONE AWARENESS

5 CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority of U.S. provisional Application No. 60/073,443 filed February 2, 1998, the disclosure of which is incorporated fully herein by reference.

10 BACKGROUND OF THE INVENTION

10 Prior art voice mail systems use series of pre-recorded messages to allow the voice mail system to interact with both incoming callers and subscribers to the voice mail system (those who have mailboxes on the system). Applications written for the voice mail system and the inputs made by incoming callers and/or subscribers determined which pre-recorded messages are played and the order in which they are played. These inputs are usually in the
15 form of DTMF (Dual Tone Multi-Frequency) tones generated when the caller or subscriber presses a button on the telephone keypad. Some of the pre-recorded messages include context related information. A common example of such a message is, "You have <number> new <message/messages>." The "<number>" portion of the message is replaced by a pre-recorded message fragment of the appropriate number for the mailbox being accessed.

20 Further, the system chooses whether to use a pre-recorded fragment for "message" or for "messages" depending on whether the numeric value of <number> is 1 or another number. Prior art voice mail systems typically use one set of prerecorded messages for all subscribers and callers. This one set of prerecorded messages also uses a single voice for all of the messages in the set. The same person (voice talent) records each of the messages.

25 A problem with the prior art voice mail systems is that different people find different speech patterns appealing. Different people tend to like and thus better understand different voice patterns. Aspects of voice patterns include fast or slow speaking, sing-songy speaking or monotonatic, pitch, dialect and the gender of the speaker. Voice patterns also can reflect different personalities of the speaker.

30 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of the telecommunications application hardware platform according to a preferred embodiment of the invention.

35 FIG. 2 is a flow chart of the process used by subscriber in conjunction with the preferred embodiment of selecting an agent for that subscriber.

DETAILED DESCRIPTION OF THE INVENTION

A block diagram of the telecommunications application hardware platform 10 used with the preferred embodiment is shown in FIG. 1. The typical telecommunications applications run on the platform include call answering (including voice, fax and data processing), multimedia messaging, voice recognition and call management. Despite having functionality beyond handling voice calls, for convenience, the telecommunications application hardware platform together with its various telecommunications applications will be referred to herein as the "voice mail system." The platform has three main elements, a series of media modules 12, a series of application modules 14 and a series of management modules 16. These three series of modules are interconnected using a dual high speed Ethernet backbones, centered around Ethernet Hub A 18 and Ethernet Hub B 20. Both Ethernet hubs are connected to an Intranet 22, which allows the platform to communicate to and receive commands from subscribers through their desktop computers and through the Intranet. Alternatively, any network other than traditional Intranets may be employed, including the Internet. A principle kept in mind in the design of the platform is the ability to offer extremely high operational availability of the platform and applications running on it.

The media modules 12 provide media storage, media flow (play/record), media transformation (Digital Signal Processing — DSP) resources and the telephony interfaces for the platform. The media module is capable of playing and recording multimedia messages (voice, fax, e-mail) from/to disk as well as supplying tone detection/generation, voice recognition, text to speech and fax modem services.

Each media module uses N+1 power and RAID disk technologies to enhance its reliability and availability. Additionally, media modules are clustered to allow failover between modules in the event one of them should fail. The operating system for the media module host CPU is Solaris.

Application modules are NT servers hosting Microsoft's Windows NT Server software. They host the applications and database services for the platform. Communication with media modules is via the media module API and remote procedure calls. Like the media modules, the application modules make use of N+1 power and RAID disks and are themselves clustered for high availability operation.

The management module is a specialized version of an application module. The management module is responsible for hosting the cluster management services and call manager application and is central point for the collection and control of the platform fault management and alarming. To support all of this, the management module contains extra hardware for connection to media module consoles (not shown), application module maintenance ports, and the system monitor. The system monitor provides fault monitoring for each of the elements of the platform as well as providing critical, major and minor relay

1 connections to the facility alarm grid. It communicates with each management module across
an RS232 link. In some configurations, the platform management services and applications
may reside on the same NT servers.

5 The backbone 18, 20 is what ties all of the modules together. Each module has dual
100 Base-T Ethernet connections that terminate at two separate Ethernet hubs 18, 20. There
is a third 10 Base-T Ethernet connection 22 between the media modules that is used for a
heartbeat for a failover mechanism.

10 A media module consists of a 20 slot VME enclosure, common control, T1 or E1
telephony interface cards, fax service circuit cards (optional), and a storage subsystem. All
of these components are packaged in a NEBs compliant cabinet enclosure.

The media module has four main components: media module enclosure power &
package; common control; telephony/DSP/service circuits; and media storage.

15 The preferred embodiments includes a pair of media modules each of which can host
up to a maximum of 240 telephony and 240 fax ports. However, alternative embodiments
include additional media modules.

The media module common control consists of the host CPU, SCSI host interfaces,
Ethernet controllers and the environmental monitor.

20 The media module host CPU is packaged in a three slot, 6U VME bus module. The
CPU requires a fourth backplane slot when Sbus modules are installed. The Sbus module
carrier is used in the preferred embodiment. For the preferred embodiment the media module
host CPU supports: Processor: Dual Hyper SPARC; Memory: 64 to 512 MB ECC DRAM;
Sbus: Two standard Sbus slots; SCSI: Two fast/narrow SCSI-2 ports; Ethernet: Two 10 Base-
T Ethernet ports; and Serial I/O: Four RS 232 ports

25 The host CPU can support several daughter board processor modules. The preferred
embodiment will use processor modules with speeds of either 125 MHz, 150 MHz, 166 MHz
or 200 MHz depending on performance requirements. Single, dual and quad processor
configurations are possible in alternate embodiments.

30 The host CPU can accommodate up to 512 MB of error correcting [ECC] memory in
increments of 64 MB. The ECC provides single bit error correction and multiple bit error
detection on a per byte basis. The amount of memory populated will depend on performance
requirements.

The media module includes a 100 Base-T Ethernet controller that connects to the 100
Base-T Ethernet hub designated as network B. This network serves as the backup network
for network A.

35 Each media module has an environmental monitor [EM] to monitor and report on the
system's condition and operating environment. The controller is a single slot VME card
which the CPU interrogates across the VME bus.

1 The environmental monitor provides: RAID power and fan status for up to 3 RAID
shelves; Media Modules cabinet temperature; VME enclosure temperature; VME backplane
voltage monitor (software readable): +5 volts, +12 volts, -12 volts; Cabinet fan status; VME
enclosure power and fan status; Control of the display panel fault LED; Signaling of media
5 module faults to a management module; Remote VME bus reset (to reset the buddy media
module); Signaling a fault to a management module for the buddy media module; Voltage
test points for VME backplane voltages; LED indicators for VME backplane voltages; and 16
LED indicators for media module fault conditions.

10 Telephone network and service circuit interface modules provide the telephony, DSP
and service circuit resources for a media module.

 The modules are made up of a base board and one or more daughter cards combined
into a single 6U VME64 module.

15 The T1/Voice module consists of four T1 spans and the DSP resources to support
basis voice functionality for 96 channels. The configuration as described below occupies a
single VME backplane slot. VME base board with an Intel i960 processor, 4 MB of DRAM
and two T1 spans; Dual span T1 daughter board; and Signal processor daughter board with
six Motorola 66 MHz 56303 DSPs.

20 The E1/Voice module consists of four E1 spans and the DSP resources to support
basis voice functionality for 90 channels. The forth span, allowing 120 channels, will be
enabled with in a future version of the hardware. The configuration as described below
occupies a single VME backplane slot. VME base board with an Intel i960 processor, 4 MB
of DRAM and two E1 spans; Dual span T1 daughter board; and Signal processor daughter
board with six Motorola 66 MHz 56303 DSPs.

25 The fax module has the processing resources to provide 24 channels of fax transmit
and receive functionality in a single VME slot.

 A fax module consists of: VME base board with an Intel i960 processor, 8 MB of
DRAM; Signal processor daughter board with six Motorola 66 MHz 56303 DSPs.

 Media storage is accomplished using a dual controller RAID system. The RAID
configuration is 0+1 (mirrored and striped).

30 The specifics of the RAID system described here are unique to the Artecon product.
Alternatively, RAID systems from other manufacturers may be used. SCSI bus termination
is done externally to the RAID controllers so that the controllers may be hot swapped without
interfering with the SCSI bus termination.

35 An application module consists of an industrial grade PC, common control, and a
storage subsystem.

1 The preferred embodiment supports two pairs of application modules and their storage
subsystems packaged in a NEBs compliant cabinet enclosure. Each pair of application
modules shares a single shelf dual controller RAID system.

5 Common control of an application module includes the host CPU, a video controller, a
SCSI controller, two Ethernet controllers and an environmental monitor.

10 The host CPU is a passive backplane single board computer with an ISA and PCI bus
interface. It is designed to plug into a PICMG compatible passive backplane that provides
both ISA and PCI card slots. For the preferred embodiment the application module host CPU
supports: Pentium Pro processor; custom BIOS; 128 MB ECC DRAM; floppy controller
port; IDE interface; and two RS232 ports.

15 The processor in the application module of the preferred embodiment is a Pentium Pro
operating at a core speed of 200 MHz and a bus speed of 66.67 MHz.

20 The BIOS contains custom extensions to allow remote serial communications with the
host when the operating system is not loaded. Communication is supported across comm
port 1. This remote preboot access permits maintenance personnel to interrogate/modify the
BIOS CMOS settings and to run diagnostics when a system is off line.

25 The host CPU can support up to 512 MB of error correcting [ECC] memory. The
preferred embodiment provides 128 MB of ECC memory. The ECC provides single bit error
correction and multiple bit error detection on a per byte basis.

30 Application modules are designed to operate without a keyboard or monitor; however,
a video controller is still required by the Windows NT operating system to allow the system
to boot. All application modules are equipped with a generic video controller. Depending on
a particular system, they may be either PCI or ISA cards. The video controller's I/O is not
routed to the bulkhead, but it is accessible from the rear of the application module chassis.

35 Each application module has two PCI bus 100 MB Ethernet interface cards. The
Ethernet interface is 100 Base-T.

40 Each application module has an environmental monitor [EM] to monitor and report on
the system's condition and operating environment. The controller is a single slot ISA bus
card which the CPU interrogates across the ISA bus.

45 The EM has a ISA slave interface that occupies 4 bytes in the ISA I/O address space.

50 The environmental monitor provides: RAID power and fan status; application module
cabinet temperature; application module cabinet fan status; PC enclosure temperature; PC
enclosure fan status; PC enclosure power status; host processor (Pentium Pro) temperature;
ISA/PCI backplane voltage monitor: +5, -5 volts, +12 volts, -12 volts; control of the cabinet's
display panel fault LED; control of the PC enclosure's thermal warning LED; signaling of
application module faults to a management module; CPU reset (to reset itself) Note: a CPU

1 reset resets all boards in the AM; remote CPU reset (to reset the buddy application module);
and signaling a fault to the management module for the buddy application module.

The application module has a PCI, differential, fast/wide SCSI-2 host controller for
connection to the RAID system. For compatibility with NT clustering, the controller's SCSI
5 ID can be changed programmatically.

Storage is accomplished using a dual controller RAID system. The RAID
configuration is 0+1 (mirrored and striped).

Again, SCSI bus termination is done externally to the RAID controllers so that the
controllers may be hot swapped without interfering with SCSI bus termination.

10 The management module uses the same components as an application module. In
addition, it has peripheral storage devices and expansion serial ports to accommodate
console/maintenance port connections and alarming.

The preferred embodiment was one pair of management modules and their storage
sub-system packaged in a NEDs compliant cabinet enclosure.

15 A second PCI SCSI host controller that interfaces to the tape drive is provided in
management module 2 16b. This controller has a single ended, fast/wide SCSI-2 interface.

A tape drive and CDROM are equipped in one of the management modules.
Failover/redundancy is not provided for in these peripheral devices.

For doing database back ups, a four millimeter SCSI, DAT tape drive is installed in
20 management module 2 16b. The tape is connected to a SCSI host controller separate from
the one used for the RAID system. The tape storage capacity is 4 GB.

For media distribution, installation and upgrade a 12x speed CDROM is installed in
management module 16a. The CDROM interfaces to the host CPU's on board IDE bus.

25 The preferred embodiment uses dual IEEE 802.3 compliant 100 MB Ethernet
networks to connect all of the internal modules. Both networks are built around 12 port 100
MB repeater hubs that connect to each of the networked modules.

Each hub has a single power supply. The hubs are connected to separate input power
feeds to allow maintenance to be performed on one of them without disturbing the other.

30 Two ports from each hub are routed to the management module's I/O bulkhead. These
provide the external network access to the cluster.

Each medial module can support a maximum of 240 telephony ports. The ports can be
either T1 or E1, but both may not be mixed within the same backplane.

For a T1 system a maximum of three 4 span line cards may be installed in each media
module. In this configuration only two of the four spans are usable on the third line card.

35 For an E1 system a maximum of three 3 span line cards may be installed in each media
module. In this configuration only two of the three spans are usable on the third line card.

1 The preferred embodiment supports a 24 port fax card. Each media module can accommodate a maximum of 10 fax cards for a total of 240 fax ports.

5 The minimum number of disks allowed in any RAID configuration is 3. In the media module the maximum number of RAID disks allowed is 15 with 14 available for storage and 1 reserved for a global spare. In the application and management modules the maximum number of RAID disks allowed is 7 with 6 available for storage and 1 reserved for a global spare. In each RAID system two slots are reserved for building new RAID sets when performing disk upgrades.

10 The platform is designed for modular hardware serviceability. The following components support live insertion/removal and may be added or replaced with no impact on system operation: media module (including RAID disk drives and controllers; VME & RAID power supplies & fans; telephone network interface modules; fax service circuits; and CDROM drive); and application module/management module (including RAID disk drives and controllers; AM/MGM & RAID power supplies & fans; and AB switch power).

15 If the need arises to replace a component that does not support hot swap, redundancy allows failing over to another resource during the maintenance period.

20 The platform provides the hardware capability to perform software upgrades without shutting the entire platform down. Upgrades are performed incrementally on each module until all modules are at the new software level. There may be some degradation in the level of service during the time a module is being upgraded.

 For upgrade purposes, a single media module may be removed from service, upgraded and returned to service with the only result being reduced port capacity during the down time interval.

25 An individual media module must be removed from service to upgrade any of the common control components.

 Network interface modules are hot-plug and may be added or removed from a media module without service interruption.

 Fax cards are hot-plug and may be added or removed from a media module with service interruption.

30 Increased storage upgrades are expected to occur with each advancement made in disk drive storage capacities. The platform architecture provides a transparent upgrade path that requires no down time to the media module being upgraded. Requirements for the upgrade are as follows: two open slots in the RAID subsystem; and all disk drives in a logical unit must be upgraded at the same time.

35 The upgrade capabilities for the application and management modules are identical.

 The application modules are configured in redundant pairs. One application module may be removed from service and upgraded without interrupting service to the cluster.

1 Application and management modules must be removed from service to service any of the common control components.

 In the preferred embodiment there is no present need to upgrade the Ethernet networks exists, however, the platform Architecture allows for network upgrades to accommodate
5 expansion in future releases. As the cluster grows, the network structure can be migrated to higher speed Ethernet, ATM or other network technologies.

 In the preferred embodiment, the application modules include the applications that supply the functionality of voice mail system that is apparent to a user of the voice mail system. As stated above, the applications typically include the functionality of call
10 answering (including voice, fax and data processing), multimedia messaging, voice recognition and call management, it can include any telecommunications functions. In the preferred embodiment, the application includes several sets of pre-recorded messages.

 All of the messages of a particular set of pre-recorded messages are recorded by the same voice talent. However, different sets of pre-recorded messages may be recorded by
15 different voice talents. Additionally, each set of pre-recorded messages is recorded by the voice talent using the same basic speed, dialect, pitch and personality. Of these different voice qualities used in recording a set of messages, personality is of importance. The same voice talent can record messages using any of a variety of distinct personalities and emotional qualities, such as happy, serious, verbose and terse. When multiple voice talents are also
20 used, the number and variety of different voice/personality combinations is considerable.

 The preferred embodiment then allows the user to select one from the various sets of pre-recorded messages stored in the application module. Once a set of pre-recorded messages is chosen, that set represents the subscriber's chosen "agent" for interacting with the voice mail system. The preferred embodiment employs a brief interview process shown
25 in FIG. 2 to allow the user to select the agent with the personality preferred by the user. When a subscriber first uses the voice mail system, or decides to change their agent, the selection process begins at entry point 30. In block 32, the system begins waiting for a voice selection response from the subscriber. At the same time, a Sample Introduction, which introduces the agents to the subscriber, is played. In one embodiment the Sample
30 Introduction follows the following script. In the following script, Agent #1 is the default agent in the case of a new subscriber, or the currently selected agent for an existing subscriber who is changing their agent.

 Agent #1: You may select among <number of voices available (n)> assistants. This is what we sound like . . .

35 Agent #1: It's either my voice, the one you've heard before . . .

 Agent #2: . . . or it's me. You can hear my voice . . .

 . . .

1 Agent #n: ... or you and your callers can hear my voice.
 Agent #1: For my voice, press 1.
 Agent #2: For my voice, press 2.

...

5 Agent #n: For my voice, press <n>.

It is noted that the phrase used to introduce each new voice (the "personality signature phrase"), such as Agent #2's "... or it's me. You can hear my voice ..." usually contains slightly different words to make up the introduction. The words used are chosen to be consistent with the agent's personality.

10 If the user responds to the Sample Introduction by pressing a key on their telephone between 1 and n, indicating a valid choice of an agent, the branch to block 34 is taken. In block 34, a message, spoken by the just-chosen agent, states, "OK, I'll be your assistant from now on." Of course, the words used by the chosen agent to communicate the choice of that agent may be different for each agent, reflecting that agent's personality. After block 34, the
 15 agent selection process exits at block 38.

 If the user does not respond to the Sample Introduction or responds with an inappropriate key (not a number between 1 and n), the path from block 32 to block 36 is taken. In block 36, a message, spoken by the prior agent (Agent #1 in the case of a new subscriber), states, "OK, I'll continue to be your assistant." Again, the words used by the
 20 chosen agent to communicate the retention of the prior agent may be different for each agent, reflecting that agent's personality. After block 36, the agent selection process exits at block 38.

 With respect to the pre-recorded messages needed to implement the agent selection process, the voice for each agent must record all of the numbers from 1 to n and each of the
 25 following phrases:

 You may select among <number of voices available (n)> assistants. This is what we sound like ...

 It's either my voice, the one you've heard before ... ;
 ["middle of list" intonation] <personality signature>;
 30 ["end of list" intonation] <personality signature>;
 For my voice, press ... ;
 OK, I'll be your assistant from now on; and
 OK, I'll continue to be your assistant.

35 Each of these phrases is needed for each agent because the current choice of agent, which could be any of the agents for a particular subscriber, determines which agent's recordings are use for each of the phrases. Again, the specific wording used by a particular agent to convey the message of each of the phrases can vary with the personality of the agent.

1 It has been found that even the short exposure to a voice and personality that is given
in the agent selection process shown in FIG. 2 supplies subscribers with a great amount of
information from which to choose a favorite agent. In particular, most subscribers can
immediate pick out their favorite voice/personality from one listening to the short personality
5 signatures provided to them. Alternatively, though, longer exposure to the different agents
can be provided. In another alternative, the system can conduct an interview process to try to
determine for the subscriber which agent is most likely to appeal to them.

As voice mail system subscribers use a particular voice mail system more often than
outside callers, the choosing of a personal agent is more important for subscribers than
10 callers. However, using ANI information contained in the data the voice mail system
receives with each incoming call that identifies the calling stations phone number, the voice
mail system can automatically use a selected agent for all calls received from a particular
phone number. Alternatively, Caller ID information or any other method of determining the
calling party's number can be used in place of or in addition to ANI information. In this way,
15 the time involved in selecting an agent by a caller can be worthwhile for callers who call the
particular voice mail system often from the same phone number. Alternatively, known voice
recognition technology can be used to identify incoming callers by analyzing the spoken
response to a system generated prompt, such as, "Hello, you've reached the office of Joe
Smith, whom may I say is calling?" The response is then processed by the voice recognition
20 software and if the caller is recognized, the caller's choice of agent is then used.

In a combination of the ANI and voice recognition methods of caller identification, a
database is provided which stores correlations between callers identified by the voice
recognition software and the number from which they have called, according to the ANI
information. Thus, when a call comes into the system, the database is first checked to see if
25 there are any entries which corresponding to the ANI information for the incoming call. If
there is only one entry for the calling number, the system answers the call, "Hello, is this Joe
Smith?" using the agent that Joe Smith has chosen before. Then, analyzing the response to
this prompt, the voice recognition software can verify that the caller's voice matches the
systems records for Joe Smith's voice. If the voice does not match, or says "No", the system
30 first checks to see if the voice of the response matches any other records in the database. If
so, the system can ask if the caller is the person in the database for the matching voice to
verify their identity. If the system does not find a match for the voice in the database, or if
the caller does not verify their identity as selected from the database, the system proceeds to
add a new entry for the caller, with both the ANI information and voice pattern information.

35 Using the same methods, a subscriber can be identified when they call into the system
from an outside telephone. In this instance, the subscriber himself or herself has an entry in
the database. This database includes the subscriber's various telephone numbers, such as

1 home, office and mobile numbers. Thus, if the system receives a call with ANI information matching any of the subscriber's various telephone numbers, there is a high likelihood that the caller is the subscriber. When an outside caller is identified by the system as a subscriber, that subscriber's agent is used to handle to call.

5 The identification methods also allow a subscriber to select an agent for anyone in their address book. This is of particular usefulness when the subscriber knows that a person in the database is more comfortable with a language different than the language used by the system's default agent. In an example of this situation where a particular caller prefers to speak French, the subscriber can have the voice mail system always use a French language agent once it has identified that caller.

10 Additionally, the voice mail system can be set up to allow outside callers who are frequent users of the voice mail system to choose an agent that is preferable to them. Again, as with the caller who prefers a different language, once the caller is identified by the voice mail system, the database is accessed and the caller's chosen agent is used for the duration of the call. In this case, though, no subscriber involvement is necessary in the selection of the preferred agent for that caller.

15 In an alternative embodiment, using known weaving technology (voice patterns of someone reading a sentence or paragraph are taken and the words/phonemes in the sample are used to make new sentences) the system can create an agent based upon the user's own voice and speech patterns. Thus, a user reads a paragraph (or however much sample is needed) and the recording of that reading is used to automatically create the pre-recorded messages for that user's agent.

20 The database that stores information about callers based on ANI information, voice recognition or a combination of these techniques allows further functionality to the voice mail system apart from the selection of a preferred agent personality. This additional functionality centers around the concept of a personal assistant, enabled by expanding the incoming caller database into a telephone user interface (TUI) address book. The address book contains phone numbers, fax numbers, other numbers, e-mail addresses and other information that will facilitate intelligent handling of calls to and from the people in the address book.

25 Each entry in the address book contains an entry number, a caller-spoken name utterance, a subscriber-spoken utterance of the entry's name, the entry's phone number, and the entry's fax number (optional). As caller messages are left for the subscriber with the voice mail system, the caller-spoken names, ANI and keyed-in phone numbers are saved with the message (if requested by the greeting option selected and given by the caller). When the subscriber has listened to a message for which at least some phone number information is available, one option that becomes available is to add this caller to the address book. If this

1 option is selected, the voice mail system will prompt the subscriber to say the spoken name of the caller, verify the phone number to be stored, and enter the fax number if available and not already entered by the caller.

5 Names may also be added manually by selecting the appropriate option under a "Setup/Address Book" menu of the voice mail application. After selecting the slot into which the entry will be placed, the subscriber-spoken utterance of the entry's name, the phone number and the fax number are entered manually.

10 Each slot in the address book is numbered, starting with one. When a person is assigned to a slot, they stay there with that number until manually deleted or replaced via the address book maintenance options (Add, Change, Delete, Review One, Review All) in the "Setup/Address Book" menu. Deletions do not reorder the list, and additions are placed in the slot number specified by the subscriber (the first available slot is suggested by the system). Any information in a slot may be replaced (Change command).

15 One function available to the system with TUI address book is calling people from the information in the address book. To call a person in the address book the subscriber presses a number associated the person. If there are 10 or more entries, the selection of the entry to dial is considered complete when the "#" key is pressed or a timeout occurs. If the number of entries is less than 10, the attempted outdial occurs immediately upon receipt of the single-digit keypress, without waiting for a timeout. The phone number from the address book is then used to dial the desired person.

20 Alternatively, the phone number for a person in the address book can be dialed when the subscriber speaks the person's name to the voice mail system, using voice recognition. In one embodiment, the voice recognition relies on the subscriber having spoken the person's name to the voice mail system when the person's address book record was created. In another embodiment, a voice recognition name template is created from the text representation of the person's name and stored as an entry in the address book. The person is then dialed by a voice command matching the voice recognition name template.

25 Another feature is automatically adding an entry to the subscriber's address book from the information stored in an incoming voice message to the subscriber. Particularly if the voice mail application prompts the caller to say their phone number at a particular point in the call, the phone number is converted into digits which are automatically stored in the caller's entry in the address book should the subscriber add the person to the address book. The address book also allows the automatic addition of a person to the subscriber's address book from the information stored in an incoming e-mail message to the subscriber.

30 The system stores extensive information about the subscriber's use of a particular entry in the Address Book as part of the entry. Thus, for example, when there is a question by the voice recognition software whether the subscriber said "John Smith" or "Joe Smith," the

1 system can make an intelligent guess that the subscriber intended to dial Joe Smith because
that subscriber calls Joe Smith once a week on average and that subscriber hasn't called John
Smith in over six months.

5 The system also stores information about the number and frequency of calls from a
particular entry in the address book as part of the entry, as well as storing information about
how the subscriber treats this caller and/or messages from this caller. With this information,
the system can predict how the subscriber will want to treat a particular call/message. For
example, if the subscriber always immediately returns calls from their mother, the voice mail
10 system presents the message from the subscriber's mother and automatically asks if the
subscriber would like the system to place a return call immediately. Alternatively, if a
subscriber routinely sends calls from a particular caller to be answered by the voice
messaging function, the system will present the call with a statement such as, "Mr. X is
calling, I will route the call to voice mail unless you press the star key . . ." The same
information can be used by the voice mail system to make an internal decision to promote an
15 address book entry to a VIP list based on subscriber's treatment of calls and messages from
that entry.

20 In an alternative embodiment, a visual graphic based computer interface is used to
communicate between the voice mail system and the subscribers in all of the functions
described above instead of using voice based menus used over the subscriber's phone as
described above.

25 Another feature of the preferred embodiment is automatically adjusting which pre-
recorded messages are played at different points in user interaction based upon the user's
competence in interacting with the system, as perceived by the voice mail system. In almost
any particular point in the interaction with a voice mail system, while there is one particular
piece of information that needs to be communicated to the user, the manner of
communicating this information can range greatly along the spectrum from terse to verbose.
Generally, experienced users prefer more terse messages while inexperienced users
appreciate more verbose messages. In a preferred embodiment, the system monitors various
parameters such as the frequency at which the user reaches a particular point in the system
30 where a message is played, errors made by the user (determined by hangups followed by
immediate return calls, backups in a menu hierarchy, etc.), multiple long pauses without user
input at the same point in the system on consecutive calls (as opposed to singular pauses
which may be the result of the user being distracted/interrupted while using the system), and
how quickly a user interrupts a message with a selection (e.g., DTMF tone).

35 A preferred embodiment allows the use of these detection criteria to be used both for
changing the message played at a local point in the system or for making global changes in
the level of message played to a particular user. This process is called flexing the prompt

1 levels and the specific way the various parameter are programmed to affect the flexing of
prompt levels is called the flex behavior of the system. Of course, the user is allowed to
override the system and manually select the terseness of messages either locally or globally.
Last, as with the selectable agent personalities, while mostly applicable to internal users of
5 the system, the invention may also be applied to incoming callers, identified by the ANI
information received with the call or any other manner of identifying the caller, including
voice recognition as discussed above.

The system also allows the fine-tuning of the flex behavior by individually setting all
of these "flex-triggers" on a state-by-state basis, allowing the application designer very
10 precise control over flex behavior throughout the application. For example, items on the main
menu, used more frequently, might flex after 5 correct uses, whereas the selection of a
greeting style (which includes a long preamble before the menu at the beginner level) might
flex after only two uses.

Further, this would also allow an entire set of flex settings to be associated with a
15 "language," allowing the designer to adjust flex behavior to be appropriate for various
languages/personalities provided with the application.

In a preferred embodiment, there are three levels of prompting and four possible
settings of a subscriber's prompt level:

Flex - this setting automatically adjusts prompts among the three available levels to
20 accommodate the subscriber's experience level at a number of pre-defined states in the
user interface, adjusting the level up (or down) as appropriate.

Training - these are explanatory prompts that provide all of the information a
subscriber might require to understand what the next appropriate response on their part
needs to be.

25 Standard - these are concise prompts, asking for the subscriber's response directly,
with little or no explanation; they assume the subscriber has progressed beyond the
"training" stage.

Advanced - these are tightly edited prompts, using only sounds or very short verbiage
to prompt for the desired response.

30 When the Flex level is selected, at pre-defined states in the user interface, the preferred
embodiment adjusts its prompts among the three available levels to match the subscriber's
level of experience with a particular activity. In any state within which prompt level is not
tracked, prompt level is inherited from its parent state.

In order to adjust prompt levels appropriately, the system tracks the subscriber's
35 experience at each of the predefined states within the call flow, adjusting in either direction
based on both usage and the length of time since the last use of the function. For example, if
the subscriber successfully completes a given action (based on valid keypresses and/or error

1 tones received) a certain number of times, the prompts are abbreviated by one level. If, on the other hand, they fail a certain number of times, or if they have not attempted this particular action for more than "n" calendar days, the prompts are lengthened by one level.

5 The flex level is also adjusted based upon a combination of the total number of times a particular menu item has been used by a subscriber and the number of uses in a recent time period by the subscriber. Thus a subscriber who has used a menu item many times in the past, but has not used it in the last three months may be given a lower flex level than a subscriber who has not use the menu item nearly as many times total, but has used the menu item ten times in the last week. On the other hand, the subscriber who has used the menu
10 item many times in the past, but has not used it in the last three months should probably be placed at more advanced flex level than a subscriber who has used the menu item only two times, but both uses were in the last month.

15 Whenever the subscriber responds to a particular prompt with silence, the Training level's version of that prompt is played next, providing more information about the response expected (no permanent adjustments are made to prompt level; this is isolated behavior on a prompt-by-prompt basis).

The subscriber has the option to lock all interaction at a certain level, regardless of experience. (In areas where lack of instruction could result in loss of information or other undesirable result, verbose prompts are given, even at the Advanced level).

20 In another embodiment of the invention the voice mail system is implemented with time zone awareness. Some prior systems in other fields have some time zone related features. For example, Windows 95 (Windows 95 is a registered trademark of Microsoft Corporation) requests the user to select their time zone when Windows 95 is installed. Thereafter, the computer is aware of its time zone, including when to change to daylight
25 saving time and back. In prior voice mail systems, messaging systems are unaware of any time zones outside of their own. If, for example, the voice mail system places a "time stamp" on an incoming message for a user, the time stamp relates to the time zone in which the voice mail system is located. The same is true for outgoing calls; a call to a given destination may not be in the same time zone as the caller, but the prior systems are unable to make the caller
30 aware of any time zone differences.

In this alternative embodiment, the "time stamp" used for incoming messages is not necessarily tied directly to the time zone of the voice mail system, but rather is tied to a fixed time zone, such as Greenwich Mean Time (GMT). At the same time, the central clock for the voice mail system is set to the fixed time zone, such as GMT. The system is then
35 programmed with the time zone that it presently is in and the difference in time between the programmed time zone and GMT is used to calculate the local time, for any purpose the local time is needed by the voice mail system. For messages, with the time stamp recorded in this

1 manner, the system then calculates the time of message deposit by a) the time that has passed
since the message was deposited (e.g., "two and a half hours ago"), b) the time at the message
depositor's location (e.g., "2:00 p.m. local time from caller's location"), c) the time at the
5 user's/subscriber's location (e.g., "3:00 a.m., your time"), and d) the time at the
user's/subscriber's normal or "home" location.

In the above examples, the time at the message depositor's location and the time at the
user's/subscriber's location are calculated by first obtaining the phone number the caller or
the user/subscriber is calling from. As discussed above, this can be done using the ANI or
Caller ID information in the incoming call. Once the incoming phone number is determined,
10 a database is consulted, which includes international telephone country codes, area codes and
even telephone prefixes and correlates these to specific time zones. In the United States, the
database must go to the prefix level of detail because there are area codes that span more than
one time zone. For the user's/subscriber's normal or "home" location, the time zone for the
user's/subscriber's normal location is entered into the system by any of a variety of ways,
15 including the voice mail system asking the user/subscriber to supply this information at the
time their mailbox/account is set up and the information being input or programmed into the
voice mail system by a system operator.

Additional functionality of this embodiment include alerting users of the system of the
local time of party whose phone number the user has just dialed. The same database
20 described above that correlates country codes, area codes and prefixes to time zones is used
by the system to determine the time zone for a dialed phone number. The system is
programmed, on a user by user basis if desired, to inform the user of the called party's time
zone always, when the called party is in a different time zone that the caller or when the time
at the called party's location is within a certain range (e.g., 10:00 p.m. to 7:00 a.m.). Utilized
25 in combination with the TUI address book, when the system informs the caller of the called
party's current time can also be programmed individually according to an individual in the
TUI address book or according to the called phone number itself. For example, the user's
mother may go to bed early and get up early, so an alert between 9:00 p.m. and 6:00 a.m. may
be appropriate. The caller's brother, on the other hand, may be a night owl and an alert
30 between 2:00 a.m. and noon may be appropriate for him. Similarly, using the same database,
the time of day for the called party in the case of outgoing calls or for the calling party in the
case of incoming calls is displayed on the display or screen of the user of the voice mail
system.

Another aspect of this embodiment, is that the priority for incoming voice mail
35 messages may be adjusted based on the time of day of the message at the caller's location.
Thus, a call placed at 2:00 a.m. from a caller may have its priority level raised. Again, the
particular circumstances or time ranges in which a message's priority may be changed based

1 on the time of day at the caller's location is adjustable at the individual or phone number
level in the TUI address book.


5 The time zone/telephone number database can be enhanced by adding city and country
information. Thus, in the case of a user calling in for messages from the road, instead of the
voice mail system simply saying, "The message was left at 3:00 a.m., your time." the system
would say, "The message was left at 3:00 a.m., your time, in Tokyo." In this manner, the
user would be provided reassurance that the voice mail system had correctly determined the
user's location and that the time information being received is accurate.

10 In another aspect of this embodiment, the time zone/telephone database is utilized in a
auto-attendant system. For example, in a message that informs the caller of the operating
hours of a customer service phone line, a caller in California may hear a message, "The
customer service line is open from 6:00 a.m. to 4:00 p.m., Pacific Standard Time." while a
caller in NewYork calling the same customer service phone line would hear the message,
"The customer service line is open from 9:00 a.m. to 7:00 p.m., Eastern Standard Time."

1 CLAIMS:

1. A telephone system comprising:
means for detecting the phone number of the phone from which an incoming call is
being made;
5 a database relating portions of phone numbers with time zones;
a clock;
means for determining the difference in time zones between a detected phone number
of a party placing an incoming call and the time zone of the party receiving the incoming call.
- 10 2. The system of claim 1 comprising means for inclusion of an indication of the
determined difference in time zones in a message related to the incoming call.
3. The system of claim 1 comprising means for communication an indication of the
determined difference in time zones to the party placing the incoming call.
- 15 4. The system of claim 1 comprising means for communication an indication of the
determined difference in time zones to the party receiving the incoming call.
5. The system of claim 1 wherein the database also relates portions of phone numbers
20 with cities and countries.
6. The system of claim 1 further comprising means for generating a message to the party
placing the incoming call that at least partially depends upon the determined difference in
time zones.

1/2



2/2





Fig. 2



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 3/50		A3	(11) International Publication Number: WO 99/39499
			(43) International Publication Date: 5 August 1999 (05.08.99)
(21) International Application Number: PCT/US99/02238 (22) International Filing Date: 2 February 1999 (02.02.99) (30) Priority Data: 60/073,443 2 February 1998 (02.02.98) US (71) Applicant (for all designated States except US): PULSEPOINT COMMUNICATIONS [US/US]; 6307 Carpinteria Avenue, Carpinteria, CA 93013 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): CASTAGNA, William, D. [US/US]; 122 Descanso Avenue, Ojai, CA 93023 (US). (74) Agent: MONROE, Wesley, W.; Christie, Parker & Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. (88) Date of publication of the international search report: 23 September 1999 (23.09.99)	

(54) Title: VOICE MAIL SYSTEM



(57) Abstract

To implement a voice mail system with time zone awareness, the phone number of the phone from which an incoming call is made is detected. After consulting a database relating portions of phone numbers with time zones, the difference in time zone between the detected telephone number of the calling party and the time zone of the call receiving party, is determined.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/02238

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04M3/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 631 949 A (MILTON STEPHEN M ET AL) 20 May 1997 (1997-05-20)	1,2,4,5
Y	column 4, line 14 - line 25	3,6
Y	US 5 539 809 A (MAYER DANIEL J ET AL) 23 July 1996 (1996-07-23)	3,6
	column 1, line 28 - line 48	
A	WO 97 50226 A (MCI COMMUNICATIONS CORP) 31 December 1997 (1997-12-31)	
A	WO 97 11413 A (PATWARDHAN RAVINDRA KRISHNAJI ;MARDHEKAR DHANANJAY VISHNU (IN); PA) 27 March 1997 (1997-03-27)	

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

13 July 1999

Date of mailing of the international search report

22/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vandevenne, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/US 99/02238

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5631949 A	20-05-1997	NONE	
US 5539809 A	23-07-1996	JP 6237300 A	23-08-1994
WO 9750226 A	31-12-1997	AU 3491397 A	14-01-1998
WO 9711413 A	27-03-1997	AU 1854997 A	09-04-1997
		CA 2175612 A	06-11-1996